

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 April 2001 (19.04.2001)


PCT

(10) International Publication Number
WO 01/26862 A1

- (51) International Patent Classification⁷: B24B 37/04 (74) Agent: PARK, Hee, Jin: 401, Miele Haus Building, 607-10 Yoksam-Dong, Kangnam-ku, Seoul 135-080 (KR).
- (21) International Application Number: PCT/KR00/01129 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (22) International Filing Date: 10 October 2000 (10.10.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
1999/21946 U 12 October 1999 (12.10.1999) KR
2000/7082 15 February 2000 (15.02.2000) KR
- (71) Applicant: HUNATECH CO., LTD. [KR/KR]; TBI, Taejon National University of Technology, 305-3, Samsung-2-dong, Dong-gu, Taejon 300-172 (KR).
- (72) Inventors: MYOUNG, Bum, Young: 101-702, Poon-grim 2nd Apt., 929, Dongchun-dong, Yeonsu-gu, Inchun 406-130 (KR). YU, Su, Nam: 115-1103, Hanbit Apt., 99, Uheun-dong, Yusung-gu, Taejon 305-333 (KR).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- (48) Date of publication of this corrected version: 6 June 2002

[Continued on next page]

(54) Title: CONDITIONER FOR POLISHING PAD AND METHOD FOR MANUFACTURING THE SAME



(57) Abstract: A conditioner for polishing pad and a method for manufacturing the same are disclosed. The conditioner comprises a substrate having formed with a plurality of geometrical protrusions of a uniformed height on at least one of its sides, and a cutting portion having a diamond layer of a uniformed thickness formed substantially on a whole surface of the side of the substrate having the geometrical protrusions. The geometrical protrusions have a flat upper surface or the upper surface may comprise a plurality of smaller geometrical protrusions formed by recessed grooves. The substrate is made from ceramic or cemented carbide materials and has a shape of a disk, a plate having multiple corner, a cup, a segment, or a doughnut with flattened upper and lower surfaces. The conditioner may further comprise a body portion being fixedly attached to the substrate at a side opposite to the side having formed with geometrical protrusions for linking the cutting portion to conditioning equipment. The cutting portion of the conditioner realized by having above shapes and structures makes

line and surface contacts with polishing pad surface. The diamond layer coated on the cutting surface strengthens the structural integrity of the cutting surface to increase the cutting performance and imparts antiwear and anti-corrosive properties to render the conditioner with a prolonged lifetime usage.

WO 01/26862 A1

WO 01/26862 A1

(15) Information about Correction:
see PCT Gazette No. 23/2002 of 6 June 2002, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.